

40850 台中市南屯區工業23路25號 No.25, Gongyequ 23rd Rd., Nantun Dist., Taichung City 40850, Taiwan TEL: +886-4-23503555 FAX: +886-4-23501867 service@puffdino.com / www.puffdino.com

Date of Revise: <u>2020/3/17</u>

Safety Data Sheet

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity PUFF DINO HIGH TEMPERATURE RESISTANCE SPRAY PAINT

Alternate Names DP56, DP57, DP58

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name PUFFDINO TRADE CO., LTD.

No.25, Gongyequ 23rd Rd, Nantun Dist, Taichung City 40850, Taiwan

Telephone +886-4-23503555 **Fax** +886-4-23501867

1.4. Emergency telephone number

Emergency phone # +886-4-23503555

Section 2. Hazard identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable aerosols 1 H222 Extremely flammable aerosol

H229 Pressurized container: may burst if heated

Gases under pressure H280 Contains gas under pressure; may explode if heated

Skin corrosion/irritation 3 H316 Causes mild skin irritation
Serious eye damage/eye H319 Causes serious eye irritation

irritation 2

2.2. Label elements

According to Regulation (EC) No 1272/2008







Danger

Precautionary Statements - Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/eye protection/face protection.

Precautionary Statements - Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Precautionary Statements - Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Precautionary Statements - Disposal:

See Technical Data Sheet.

2.3. Other hazards

This product contains no PBT/vPvB chemicals.

Section 3. Composition/information on ingredients

3.2. Mixtures

If the product contains substances that present a hazard according to Regulation (EC) No. 1272/2008 [CLP/GHS] (as amended by (EU) 2015/830), they are listed below.

Ingredient/Chemical Designations		Weight %	EC No. 1272/2008 Classification*	
Polysiloxane				
CAS Number:	63148-53-8	20. 25	Net Classified	
EC No.		20 - 25	Not Classified	
Index No.:				
N-Butyl Acetate				
CAS Number:	123-86-4	10 - 15	Flam. Liq. 3;H226	
EC No.	204-658-1	10 - 15	STOT SE 3;H336	
Index No.:	607-025-00-1			
Butanone			Flow Lin 2011225	
CAS Number:	78-93-3	40.45	Flam. Liq. 2;H225	
EC No.	201-159-0	10 - 15	Eye Irrit. 2;H319 STOT SE 3;H336	
Index No.:	606-002-00-3		3101 35 3,11330	
Dimethyl ether				
CAS Number:	115-10-6	40. 45	Flows Con Addition	
EC No.	204-065-8	40 - 45	Flam. Gas 1;H220	
Index No.:	603-019-00-8			

^{*}The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious, place in the recovery position and obtain immediate medical

attention. Give nothing by mouth.

Eye contact Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek

medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized

contact skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

5.2. Special hazards arising from the substance or mixture

Contains gas under pressure; may explode if heated

Hazardous decomposition: Carbon Dioxide, Carbon Monoxide

Keep away from heat/sparks/open flames/hot surfaces - No smoking.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/light/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from firefighting to enter drains or water ways.

Put on appropriate personal protective equipment (see section 8).

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Small Spill: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Large Spill: Flush spill area with water spray. Prevent runoff from entering drains, sewers, or streams. Dike for late disposal.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Section 7. Handling and storage

7.1. Precautions for safe handling

Store in cool, dry ventilated area. Avoid excessive heat. Always keep containers tightly closed when not in use. Avoid contact with eyes. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong acids and oxidizing agents

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No available information

Section 8. Exposure controls/personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value	
		OSHA	No Established Limit	
63148-53-8	Polysiloxane	ACGIH	No Established Limit	
		NIOSH	No Established Limit	
	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m³)	
123-86-4		ACGIH	TWA: 20 ppm	
		NIOSH	TWA 150 ppm (710 mg/m ³) ST 200 ppm (950 mg/m ³)	
	Butanone	OSHA	TWA 200 ppm (590 mg/m³)	
78-93-3		ACGIH	TWA: 50 ppm STEL: 100 ppm	
		NIOSH	TWA 200 ppm (590 mg/m ³) ST 300 ppm (885 mg/m ³)	
		OSHA	No Established Limit	
115-10-6	Dimethyl ether	ACGIH	TWA: 1000 ppm	
		NIOSH	No Established Limit	

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate,

certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of

Controls local exhaust ventilation and good general extraction. If these are not sufficient to maintain

concentrations of particulates and any vapor below occupational exposure limits suitable

respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using

Practices toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid

Odor No available information
Odor threshold No available information
pH No available information
Melting point / freezing point No available information
Initial boiling point and boiling range No available information

Flash Point -41°C (-41.8°F)/Test method: closed cup

Evaporation rate (Ether = 1) No available information

Flammability (solid, gas) Gas

Upper/lower flammability or explosive limits Lower Explosive Limit: 1.7%

Upper Explosive Limit: 7.6%

Vapor pressure 518.9 kPa (20°C)

Vapor Density (Air=1) 1.6

Relative density

No available information

Solubility in Water insoluble

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

No available information

9.2. Other information

No other relevant information.

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No available information

10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F.

10.5. Incompatible materials

Strong acids and oxidizing agents

10.6. Hazardous decomposition products

Oxides of Carbon

Section 11. Toxicological information

11.1. Information on toxicological effects

Product

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Components

Acute toxicity

Component	Oral LD50,	Skin LD50,	Inhalation	Inhalation	Inhalation
	mg/kg	mg/kg	Vapor LC50,	Dust/Mist LC50,	Gas LC50,
			mg/L/4hr	mg/L/4hr	ppm
Polysiloxane -	No data	No data	No data	No data	No data
(63148-53-8)	available	available	available	available	available
N. Butyl Apototo	10,760.00, Rat	17,600.00,	No data	No data	No data
N-Butyl Acetate -	- Category: NA	Rabbit -	available	available	available
(123-86-4)		Category: NA			
770.00	2,054.00, Rat -	6,480.00,	32.00, Mouse -	No data	No data
Butanone - (78-93-	Category: 5	Rabbit -	Category: NA	available	available
3)		Category: NA			
Dimethyl ether -	No data	No data	308.00, Rat -	No data	No data
(115-10-6)	available	available	Category: NA	available	available

Carcinogen Data

CAS No. Component Source Value

63148-53-8	Polysiloxane	OSHA	Regulated Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IADO	Group 1: No; Group 2a: No; Group 2b: No; Group	
		IARC	3: No; Group 4: No	
	N-Butyl Acetate	OSHA	Regulated Carcinogen: No	
123-86-4		NTP	Known: No; Suspected: No	
123-60-4		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group	
			3: No; Group 4: No	
	Butanone	OSHA	Regulated Carcinogen: No	
78-93-3		NTP	Known: No; Suspected: No	
76-93-3		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group	
			3: No; Group 4: No	
115-10-6	Dimethyl ether	OSHA	Regulated Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IADO	Group 1: No; Group 2a: No; Group 2b: No; Group	
		IARC	3: No; Group 4: No	

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Commonant	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,	3hr IC50 Bacteria,	
Component	mg/L	mg/L	mg/L	mg/L	
Polysiloxane -	Not Available	Not Available	Not Available	Not Available	
(63148-53-8)	Not Available	Not Available	Not Available	Not Available	
N. Dutul Apototo	18.00, Pimephales	44.00, Daphnia sp	246.00 (72 hr),		
N-Butyl Acetate - (123-86-4)	promelas		Pseudokirchnerella	Not Available	
			subcapitata		
	2,993.00, Pimephales	308.00, Daphnia magna	2,029.00 (96 hr),		
Butanone - (78-93-3)	promelas		Pseudokirchnerella	Not Available	
			subcapitata		
Dimethyl ether -	1,783.04, Fish	755.549, Daphnia sp	154.917 (96 hr), Algae	Not Available	
(115-10-6)				INUL AVAIIADIE	

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

No available information

12.4. Mobility in soil

No available information

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No available information

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

	ADR/RID (Land	IMDG (Sea	ICAO-TI/IATA-DGR	ADN (Inland
	transport)	Transportation)	(Air transport)	waterway transport)
14.1. UN	1950	1950	1950	Not Applicable
number	1930	1950	1950	Not Applicable
14.2. UN	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable	
proper	·		· ·	Niet Annlinebie
shipping	(each not exceeding 1	(each not exceeding 1	(each not exceeding 1	Not Applicable
name	L capacity)	L capacity)	L capacity)	
14.3.		Not Applicable		
Transport	0.4	. totr priodo.o	Not Applicable	Niet Anntieckie
hazard	2.1	Sub Class: Not	Not Applicable	Not Applicable
class(es)		Applicable		
14.4. Packing	Not Applicable	Not Applicable	Not Applicable	Not Applicable
group	Not Applicable	Not Applicable	Not Applicable	Not Applicable
14.5.				
Environmental	Not Applicable	Marine Pollutant: No	Not Applicable	Not Applicable
hazards				

14.6. Special precautions for user

No further information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Section 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU Legislation

REGULATION (EU) 2015/830 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

US federal regulations

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA): All components of this material are either listed or exempt from listing on the TSCA Inventory.

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA (311/312) REPORTABLE GHS HAZARD CLASSES: Flammable (gases, aerosols, liquids, or solids),

Gas under Pressure, Simple Asphyxiant

SARA (313) TOXIC RELEASE INVENTORY: This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

National Legislation

None noted.

Taiwan (R.O.C) Legislation

Occupational Safety and Health Act, Toxic Chemical Substance Control Act, Standards of Permissible Exposure Limits of Airborne Hazardous Substances in Workplace, Regulations for the Labeling and Hazard Communication of Hazardous Chemicals, Regulations Governing Designating and Handling of Priority Management Chemicals, Methods and Facilities Standards for the Storage, Clearance and Disposal of Industrial Waste, Public Hazardous Substances & Flammable Pressurized Gases Establishment Standards & Safety Control Regulations.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

End of Document